

Effect of finite Weissenberg number on turbulent channel flows of an elastoviscoplastic fluid

Daulet Izbassarov^{1,2}, Marco E. Rosti³, Luca Brandt¹, Outi Tammisola^{1†}

¹FLOW and SeRC, Department of Engineering Mechanics, KTH Royal Institute of Technology, Stockholm, Sweden

²Department of Mechanical Engineering, Aalto University, FI-00076 Aalto, Finland

³Complex Fluids and Flows Unit, Okinawa Institute of Science and Technology Graduate University, 1919-1 Tancha, Onna-son, Okinawa 904-0495, Japan

(Received 14 October 2021)

Direct numerical simulations are carried out to study the effect of finite Weissenberg number up to $Wi = 16$ on laminar and turbulent channel flows of an elastoviscoplastic (EVP) fluid, at a fixed bulk Reynolds number of 2800. The incompressible flow equations are coupled with the evolution equation for the EVP stress tensor by a modified Saramito model that extends both the Bingham viscoplastic and the FENE-P viscoelastic models. In turbulent flow, we find that drag decreases with both Bingham and Weissenberg numbers, until the flow laminarises at high enough elastic and yield stresses. Hence, a higher drag reduction is achieved than in the viscoelastic flow at the same Weissenberg number. The drag reduction persists at Bingham numbers up to 20, in contrast to viscoplastic flow, where the drag increases in the laminar regime compared to a Newtonian flow. Moreover, elasticity affects the laminarization of an EVP flow in a non-monotonic fashion, delaying it at lower and promoting it at higher Weissenberg numbers. A hibernation phenomenon is observed in the EVP flow, leading to large changes in the unyielded regions. Finally, plasticity is observed to affect both low- and high-speed streaks equally, attenuating the turbulent dissipation and the fragmentation of turbulent structures.

1. Introduction

The manuscript considers unsteady and turbulent channel flows of non-Newtonian viscoelastic and elastoviscoplastic fluids. The dynamics of non-Newtonian turbulence has attracted a growing interest due to numerous industrial applications dealing with non-Newtonian fluids. Real industrial and natural fluids often present several non-Newtonian effects at the same time, such as plasticity (yield stress) and elasticity. Turbulent flows of yield-stress fluids are found in several industries such as petroleum, paper, mining and sewage treatment (Hanks 1963, 1967; Maleki & Hormozi 2017). Highly inertial flows of elastoviscoplastic fluids can also be found in geophysical applications, such as mudslides and the tectonic dynamics of the Earth (Oishi *et al.* 2017).

Yield-stress fluids behave like solids below a local stress threshold, and flow like liquids above this threshold. Assuming that the material is a rigid solid at stresses lower than the yield stress, purely viscoplastic models are obtained, such as the Bingham model (Bingham 1922), where the solvent viscosity of the yielded fluid flow follows a Newtonian law, and the Herschel-Bulkley model (Herschel & Bulkley 1926), where the yielded fluid

† Email address for correspondence: outi@mech.kth.se

flow is shear-thinning. However, many yield-stress fluids deform like elastic solids in the unyielded state and behave as viscoelastic liquids in the yielded state, displaying elastic (E), viscous (V) and plastic (P) properties.

A simple dynamic elastoviscoplastic (EVP) constitutive model that can be integrated with direct numerical simulations was proposed by Saramito (2007). The model has proven to capture viscoplastic and elastic effects (Cheddadi *et al.* 2011; Fraggedakis *et al.* 2016) and to properly match experimental results and observations (Holenberg *et al.* 2012) (common materials used to study this type of EVP fluids are Carbopol solutions and liquid foams Firouznia *et al.* 2018; Zade *et al.* 2020). The model was extended by the same author to account for shear-thinning effects (Saramito 2009), combining the Oldroyd viscoelastic model with the Herschel-Bulkley viscoplastic model, with a power law index that allows a shear-thinning behavior in the yielded state. When the index is equal to unity, the model reduces to the one proposed in his previous work, i.e., Saramito (2007). Apart from the models proposed by Saramito, many other elastoviscoplastic models exist in the literature. The interested reader is referred to Crochet & Walters (1983); Balmforth *et al.* (2014); Saramito & Wachs (2016); Saramito (2016); Saramito & Wachs (2017) for a thorough review of models and numerical methods.

Turbulent flow of purely viscoelastic fluids has gained attention in the drag reduction and flow control communities, since a tiny amount of polymers (parts per million) has proven efficient in reducing friction drag in pipe flows (Virk 1971). Drag reduction by polymers is related to their ability to modify coherent structures in wall-bounded turbulence (Dubief *et al.* 2004, 2005). Polymers influence the turbulent cycle in two ways: they attenuate near-wall vortices, but at the same time they also increase the streamwise kinetic energy of the near-wall streaks. The net balance of these two opposite actions leads to a self-sustained drag-reduced turbulent flow. More recently, Xi & Graham (2010, 2012a,b) proposed that polymeric drag reduction is a time-dependent process: turbulent flows with polymers spend relatively more time in hibernating phases, where the turbulence is weak, and less time in active phases with strong turbulence. The turbulent coherent structures, streamwise vortices and streaks, were found to differ in appearance depending on whether the flow was in active or a hibernating phase. Biancofiore *et al.* (2017) examined the secondary instability of streaks in viscoelastic flows, showing that the streaks reach a lower average energy with increasing elasticity due to a resistive polymer torque that opposes the streamwise vorticity and, as a result, opposes the lift-up mechanism. Numerous studies have addressed the topic of polymeric drag reduction and all cannot be reviewed here for brevity; the interested reader is referred to (White & Mungal 2008) for a thorough introduction to this subject.

Turbulent flow of yield-stress fluids (plasticity) has been studied much less, despite its relevance for applications. The reason is twofold. Time-resolved measurements in yield-stress fluids are very challenging, even in laminar flows. Most real-life yield-stress fluids are opaque and hence do not provide optical access. The transparent lab fluid Carbopol, often used in these experiments, needs careful preparation to achieve well-controlled properties (Tabuteau *et al.* 2018; Dinkgreve *et al.* 2018), and exhibits slip on smooth surfaces that needs to be avoided or carefully controlled (Firouznia *et al.* 2018). On the other hand, direct numerical simulations of yield-stress fluids have not been affordable until recently. Rosti *et al.* (2018a) first studied the turbulent channel flow of a yield-stress fluid in a near-viscoplastic limit using the Saramito elastoviscoplastic model (Saramito 2007), adding a tiny amount of elasticity to achieve numerical stability (the Weissenberg number was $Wi = 0.01$). When Bingham number was gradually increased from zero, the flow became less turbulent and more correlated in the streamwise direction, until it completely relaminarized at $Bi = 2.8$. The velocity correlations revealed that the size and

length of the near-wall streaks increased with the Bingham number. The friction factor decreased with the Bingham number in the turbulent regime, while it increased with the same in the laminar regime. Le Clainche *et al.* (2020) analysed further the simulation data of Rosti *et al.* (2018a) using High-Order Dynamic Mode Decomposition (HODMD), and compared the modes to those in Newtonian fluids, and also in purely viscoelastic fluids. Their results indicated that elasticity and plasticity have similar effects on the coherent structures; in both cases, the flow is dominated by long streaks disrupted by rapid, localized perturbations. The Newtonian flow, on the other hand, displays short streaks and more chaotic dynamics. Very recent experiments in a duct flow of Carbopol confirmed that the energy content at low wavenumbers and streamwise anisotropy were higher than in Newtonian turbulence (Mitishita *et al.* 2021), indicating that streamwise near-wall structures (streaks) were enhanced in Carbopol. These experiments at higher Reynolds numbers also confirmed the qualitative changes that viscoplasticity causes in mean flow profiles and Reynolds stresses, as observed by Rosti *et al.* (2018a).

In addition, many earlier direct numerical simulation studies addressed the turbulence in Bingham pseudoplastic fluids (obtained by regularizing the Bingham model by a large viscosity) (Rudman & Blackburn 2006; Guang *et al.* 2011; Zhu *et al.* 2020), and their shear-thinning version, regularized Herschel-Bulkley fluids by Rudman *et al.* (2004); Singh *et al.* (2017). Very recently, Zhu *et al.* (2020) studied the turbulence of a Bingham pseudoplastic fluid in a vertical channel with particles, at a higher bulk Reynolds number ($Re_b = 8000$) than Rosti *et al.* (2018a). They also obtained a drag reduction with an increasing Bingham number, along with an increasing streamwise coherence of the flow structures. They also observed that the turbulent statistics were asymmetric with respect to the centerline at higher Bingham numbers.

Transitional flows of yield-stress fluids in pipes and channels have been addressed in many studies, both experimentally and computationally. Asymmetric mean flow profile is a characteristic feature observed in pipe flow experiments of yield-stress fluids (Escudier *et al.* 2005; Peixinho *et al.* 2005; Esmael & Nouar 2008; Guzel *et al.* 2009), and for fluids with a Herschel-Bulkley-type rheology (Escudier & Presti 1996). According to Esmael & Nouar (2008), this was caused by an asymmetric nonlinear coherent structure consisting of two counter-rotating vortices. Experiments on laminar steady flow of a yield-stress fluid in a duct laden with particles were performed recently by Zade *et al.* (2020). Computational studies on transitional flows have mainly focused on linear and nonlinear stability of channel flows (Frigaard *et al.* 1994; Nouar & Frigaard 2001; Frigaard & Nouar 2003; Nouar *et al.* 2007; Metivier *et al.* 2010; Nouar & Bottaro 2010; Bentrud *et al.* 2017). Most importantly, within the Bingham model, the central plug regions of a channel flow remain unyielded despite linear perturbations, and hence the flow is always linearly stable. In non-modal analysis, in contrast to Newtonian fluids, the optimal disturbance is found to be an oblique wave (Nouar *et al.* 2007), associated with the lift-up effect (Schmid 2007; Brandt 2014). However, Nouar & Bottaro (2010) found that a slightly perturbed mean flow profile supports exponential amplification of streamwise travelling waves, indicating another possible transition scenario for the plane channel flow of a yield-stress fluid.

Concluding, all previous studies on EVP turbulence focused on either purely viscoelastic or near-viscoplastic fluids. The questions remains what happens when both elasticity and plasticity effects are finite and interact with each other. The recent experimental study by Mitishita *et al.* (2021) also raised the question how the findings of Rosti *et al.* (2018c) would be affected by finite elasticity. The present study focuses on elastoviscoplastic fluids at finite Weissenberg numbers, i.e., fluids with finite visco-elasticity and yield stress.

In this work, we perform direct numerical simulations of turbulent channel flows of




Figure 1: Sketch of the computational domain. XY and ZY planes in the middle of the domain show instantaneous streamwise velocity contours with the scale ranging from 0 (blue) to $1.27U_b$ (red). Green structures represent unyielded regions.

an incompressible elastoviscoplastic fluid and extend the one by Rosti et al. (2018c) by considering a wide range of the Weissenberg numbers $0 \leq Wi \leq 16$ and Bingham numbers $0 \leq Bi \leq 22.4$, all at the bulk Reynolds number $Re = 2800$. The non-Newtonian flow is simulated by solving the full unsteady incompressible Navier-Stokes equations coupled with a modified version of the model proposed by Saramito (2007) for the evolution of the additional elastoviscoplastic stress tensor.

The manuscript is organised as follows. In section 2, we first discuss the flow configuration and the governing equations, and then present the numerical methodology used. The new model with some test cases is reported in section 2.1, while the new results are presented in section 3. In particular, we discuss the role of elasticity and plasticity on a turbulent channel flow. Finally, a summary of the main findings and conclusions are collected in section 5.

2. Formulation

We consider the laminar and turbulent flows of an incompressible elastoviscoplastic fluid through a plane channel with two impermeable rigid walls. Figure 1(a) shows a sketch of the geometry and the Cartesian coordinate system, where x , y and z (x_1 , x_2 , and x_3) denote the streamwise, wall-normal and spanwise coordinates, while u , v and w (u_1 , u_2 , and u_3) denote the respective components of the velocity field. The lower and upper stationary impermeable walls are located at $y = 0$ and $2h$, respectively, where h represents the channel half height.

The fluid motion is governed by the conservation of momentum and the incompress-

ibility constraint:

$$\frac{\partial u_i}{\partial t} + \frac{\partial u_i u_j}{\partial x_j} = \frac{1}{\rho} \frac{\partial \sigma_{ij}}{\partial x_j}, \quad (2.1a)$$

$$\frac{\partial u_i}{\partial x_i} = 0, \quad (2.1b)$$

where ρ is the fluid density and σ_{ij} the total Cauchy stress tensor, which is written as $\sigma_{ij} = -p\delta_{ij} + 2\mu_f D_{ij} + \tau_{ij}$, where p is the pressure, μ_f the fluid molecular dynamic viscosity (also called solvent viscosity), δ the Kronecker delta and D_{ij} the strain rate tensor defined as $D_{ij} = (\partial u_i / \partial x_j + \partial u_j / \partial x_i) / 2$. The additional elastoviscoplastic stress tensor τ_{ij} accounts for the non-Newtonian behavior of the fluid, here described by a modified version of the model proposed by Saramito (2007). In the original model, when the stress σ is below the yield stress τ_0 , the system predicts only recoverable Kelvin-Voigt viscoelastic deformations, while when the stress exceeds the yield value τ_0 , the fluid behaves as an Oldroyd-B viscoelastic fluid. Thus, the total strain rate $\dot{\epsilon}$ is shared between an elastic contribution $\dot{\epsilon}_e$ and a plastic one $\dot{\epsilon}_p$ (Cheddadi et al. 2011). Since the Oldroyd-B model assumes infinitely stretched dumbbells, the range of application of the model is limited to low elasticity. To overcome this drawback, we instead use the FENE-P model. Thus, the instantaneous values of all the components of the stress tensor τ_{ij} are found by solving the following transport equation

$$\lambda \left(\frac{\partial \tau_{ij}}{\partial t} + \frac{\partial u_k \tau_{ij}}{\partial x_k} - \tau_{kj} \frac{\partial u_i}{\partial x_k} - \tau_{ik} \frac{\partial u_j}{\partial x_k} \right) + F f \tau_{ij} + \left(\frac{\partial \ln F}{\partial t} + \frac{\partial u_k \ln F}{\partial x_k} \right) (\lambda \tau_{ij} + \mu_m \delta_{ij}) = 2\mu_m D_{ij}, \quad (2.2)$$

where

$$F = 1 + \frac{\left(3 + \frac{\lambda}{\mu_m} \tau_{ii} \right)}{L^2}, \quad f = \max \left(0, \frac{|\tau_d| - \tau_0}{|\tau_d|} \right). \quad (2.3)$$

Here, λ is the relaxation time, μ_m is an additional viscosity, L is the maximum polymer extensibility, τ_0 the yield stress and $|\tau_d|$ represents the second invariant of the deviatoric part of the added stress tensor. The elastoviscoplastic parameters μ_f , μ_m , λ and τ_0 can be obtained by experimental data following the procedure detailed by Fraggadakis et al. (2016), based on the determination of the linear material functions, i.e., the storage modulus G' and the loss modulus G'' . The above constitutive equation gives a Kelvin-Voigt solid in the limit $F \approx 1$, which is the case in the unyielded state, and a behavior like a FENE-P fluid in the yielded state. The previous equation can be rewritten in terms of the conformation tensor C_{ij} as

$$\frac{\partial C_{ij}}{\partial t} + \frac{\partial u_k C_{ij}}{\partial x_k} - C_{kj} \frac{\partial u_i}{\partial x_k} - C_{ik} \frac{\partial u_j}{\partial x_k} = -\frac{f}{\lambda} (F C_{ij} - \delta_{ij}), \quad (2.4)$$

where the elastoviscoplastic stress tensor τ_{ij} is related to the conformation tensor by the relation

$$\tau_{ij} = \frac{\mu_m}{\lambda} (F C_{ij} - \delta_{ij}). \quad (2.5)$$

We use the log conformation method to overcome the well known high Weissenberg number problem (Fattal & Kupferman 2004; Hulsen et al. 2005; Izbassarov & Muradoglu 2015; De Vita et al. 2018). In this approach, equation (2.4) is rewritten in terms of the logarithm of the conformation tensor through an eigen-decomposition, i.e., $\Psi = \log \mathbf{C}$,

which ensures the positive definiteness of the conformation tensor. The core feature of the formulation is the decomposition of the gradient of the divergence free velocity field $\partial u_j / \partial x_i$ into two anti-symmetric tensors, Ω_{ij} (pure rotation) and N_{ij} , and into a symmetric tensor, B_{ij} , which commutes with the conformation tensor, i.e.,

$$\frac{\partial u_j}{\partial x_i} = \Omega_{ij} + B_{ij} + N_{ij} C_{ji}. \quad (2.6)$$

The modified transport equation to be solved is thus

$$\frac{\partial \Psi_{ij}}{\partial t} + \frac{\partial u_k \Psi_{ij}}{\partial x_k} - (\Omega_{ik} \Psi_{kj} - \Psi_{ik} \Omega_{kj}) - 2B_{ij} = \frac{f}{\lambda} \left((e^{-\Psi})_{ij} - F \delta_{ij} \right). \quad (2.7)$$

Once this equation is solved, the conformation tensor can be obtained using the inverse transformation $\mathbf{C} = e^{\Psi}$.

Finally, the full system of equations can be rewritten in a non-dimensional form as

$$Re \left(\frac{\partial u_i}{\partial t} + \frac{\partial u_i u_j}{\partial x_j} \right) = \frac{\partial}{\partial x_j} (-p \delta_{ij} + 2\beta D_{ij} + \tau_{ij}), \quad (2.8a)$$

$$\frac{\partial u_i}{\partial x_i} = 0, \quad (2.8b)$$

$$\frac{\partial \Psi_{ij}}{\partial t} + \frac{\partial u_k \Psi_{ij}}{\partial x_k} - (\Omega_{ik} \Psi_{kj} - \Psi_{ik} \Omega_{kj}) - 2B_{ij} = \frac{f}{Wi} \left((e^{-\Psi})_{ij} - F \delta_{ij} \right), \quad (2.8c)$$

$$F = 1 + \frac{\left(3 + \frac{Wi}{1 - \beta} \tau_{ii} \right)}{L^2}, \quad f = \max \left(0, \frac{|\tau_d| - Bi}{|\tau_d|} \right), \quad (2.8d)$$

$$\tau_{ij} = \frac{(1 - \beta)}{Wi} \left(F (e^{\Psi})_{ij} - \delta_{ij} \right), \quad (2.8e)$$

where we have used the same symbols to define the non-dimensional variables for simplicity. Four non-dimensional numbers appear in the previous set of equations: the Reynolds number Re , the Weissenberg number Wi , the Bingham number Bi and the viscosity ratio β , defined as $Re = \rho U \mathcal{L} / \mu_0$, $Bi = \tau_0 \mathcal{L} / \mu_0 U$, $Wi = \lambda U / \mathcal{L}$ and $\beta = \mu_f / \mu_0$, where U and \mathcal{L} are a characteristic velocity and length scales of the flow, ρ the fluid density and μ_0 the total viscosity, i.e., $\mu_0 = \mu_f + \mu_m$.

The equations of motion are solved with an extensively validated in-house code (Izbassarov et al. 2018; Rosti et al. 2018c; De Vita et al. 2018; Rosti & Brandt 2017; Shahmardi et al. 2019; Alghalibi et al. 2019). The governing equations are discretised with the second-order centered finite difference scheme on a staggered uniform grid, except for the advection term in equation (2.7) where the fifth-order WENO (weighted essentially non-oscillatory) scheme is adopted (Shu 2009; Sugiyama et al. 2011). The time integration is performed with a fractional-step method (Kim & Moin 1985) and a third-order explicit Runge-Kutta scheme except for the elastoviscoplastic stress term which is advanced with the Crank-Nicolson method.

In all the simulations, periodic boundary conditions are used in the streamwise and spanwise directions, while the no-slip and no-penetration boundary conditions are enforced on the solid walls. For all the turbulent cases considered hereafter with a bulk Reynolds number equal to $Re_b = 2800$, the equations of motion are discretised by using $1728 \times 576 \times 864$ grid points on a computational domain of size $6h \times 2h \times 3h$ in the streamwise, wall-normal and spanwise directions, with the resolution satisfying the constraint $\Delta x^+ = \Delta y^+ = \Delta z^+ < 0.6$, where the superscript $+$ indicates the wall units. The spatial resolution has been chosen equal to the one used in a previous work (Rosti et al. 2018a)




Figure 2: Time evolution of $\tau_{11} - \tau_{22}$ in an uniaxial elongation for $Bi = 1$ and $\beta = 0$: (a) the effect of Wi for $L^2 = \infty$ (Oldroyd-B model) and (b) the effect of L^2 (FENE-P model) for $Wi = 0.75$. The stress components are normalised with $\mu_0 \dot{\epsilon}_0$.

in order to properly resolve the turbulent scales as well as the unyielded plug regions which form intermittently in the domain, and verified a posteriori with a grid refinement study. In the low-Reynolds fully-laminar cases, the spatial resolution was relaxed and the domain size in the homogeneous directions reduced. Finally, all the turbulent cases are initialized with a fully developed channel flow with zero elastoviscoplastic stress ($\tau_{ij} = 0$); after the flow and stresses have reached a statistically steady state, the calculations are continued for an interval of about 500 bulk time units, during which the statistics are computed.

2.1. Validations of the FENE-P based EVP model

The present implementation for single and multiphase flows of an elastoviscoplastic fluid has been extensively validated in the past; here we report further test cases of the new FENE-P based EVP model also to present its rheological behaviour.

First, we consider a three-dimensional uniaxial elongational flow, with a constant elongational rate $\dot{\epsilon}_0$: the Weissenberg number $Wi = \lambda \dot{\epsilon}_0$ and extensibility parameter L^2 are varied in the range of $0.25 \leq Wi \leq 0.75$ and $10 \leq L^2 \leq \infty$, respectively, while the Bingham number $Bi = \tau_0 / (\mu_0 \dot{\epsilon}_0) = 1$ and the viscosity ratio $\beta = 0$. The fluid flow is assumed to have a constant velocity gradient $\partial u_i / \partial x_j = \text{diag}\{1, -1/2, 1/2\}$ and equation (2.2) can be simplified as

$$Wi \frac{d\tau_{11}}{dt} + (fF - 2Wi)\tau_{11} - \frac{d \ln F}{dt} (Wi\tau_{11} + 1 - \beta) = 2(1 - \beta), \quad (2.9a)$$

$$Wi \frac{d\tau_{22}}{dt} + (fF + Wi)\tau_{22} - \frac{d \ln F}{dt} (Wi\tau_{22} + 1 - \beta) = \beta - 1, \quad (2.9b)$$

$$Wi \frac{d\tau_{33}}{dt} + (fF + Wi)\tau_{33} - \frac{d \ln F}{dt} (Wi\tau_{33} + 1 - \beta) = \beta - 1, \quad (2.9c)$$

with $\tau_{ii}(0) = 0$ for $i = 1, 2$ and 3. The time evolution of $\tau_{11} - \tau_{22}$ (the normal stress difference) is reported in figure 2; we observe that, initially the stress components grow linearly, but when the stress level is above a threshold, i.e., the yield stress, the Saramito model ($L^2 = \infty$) predicts an unbounded growth for $Wi > 0.5$, while the FENE-P based model exhibit a limited growth with the stress difference reaching a plateau. This example




Figure 3: Steady shear viscosity for $\beta = 0$ and (a) $L^2 = \infty$ (Oldroyd-B model); (b) $L^2 = 100$ (FENE-P model).

easily explains the reason why the FENE-P based model is chosen for the current work, where we aim to investigate the effect of finite elasticity.

Next, we consider a simple constant shear flow, with shear rate $\dot{\gamma}_0$; the Weissenberg number is varied $Wi = \lambda \dot{\gamma}_0$ in the range $0.01 \leq Wi \leq 100$, while the Bingham number $Bi = \tau_0/(\mu_0 \dot{\gamma})$ assumes 4 distinct values and the viscosity ratio $\beta = 0$. We consider two cases, with $L^2 = 100$ and $L^2 = \infty$ to study the properties of the two models. For this two-dimensional problem, we have $\partial u_i / \partial x_j = \begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix}$ and equation (2.2) can be rewritten as

$$Wi \frac{d\tau_{11}}{dt} - 2Wi\tau_{12} + fF\tau_{11} - \frac{d \ln F}{dt} (Wi\tau_{11} + 1 - \beta) = 0, \quad (2.10a)$$

$$Wi \frac{d\tau_{22}}{dt} + fF\tau_{22} - \frac{d \ln F}{dt} (Wi\tau_{22} + 1 - \beta) = 0, \quad (2.10b)$$

$$Wi \frac{d\tau_{12}}{dt} - Wi\tau_{22} + fF\tau_{12} - \frac{d \ln F}{dt} (Wi\tau_{12}) = 1 - \beta, \quad (2.10c)$$

with $\tau_{ij}(0) = 0, i = 1, 2$. The dimensionless steady shear viscosity $\mu_s/\mu_0 = \beta + \tau_{12}/\dot{\gamma}$ as a function of Wi are reported in figure 3. As expected, both models exhibit a shear thinning behaviour: in particular, for $L^2 = \infty$ the model tends to a plateau at both low ($Wi \lesssim 0.1$) and high ($Wi \gtrsim 10$) Weissenberg numbers, while for $L^2 = 100$ the steady shear viscosity reaches a plateau at low Wi but it decreases monotonically at high Wi . Note that, the shear thinning effect is controlled by Bi which modifies the plateau value at low Wi .

3. Results

3.1. Laminar flow

Our first analysis considers the laminar flow of an elastoviscoplastic fluid. All laminar cases are fixed at $\beta = 0.9$, $Re = 2800$ and $L^2 = 3600$, while the Weissenberg and the Bingham numbers are varied in the range of $0.01 \leq Wi \leq 16$ and $0.1 \leq Bi \leq 100$, respectively. Note that the domain size in the homogeneous directions was kept very




Figure 4: Fanning factor as a function of (a) the Weissenberg number for $Bi = 0.1, 2.8, 11.2$ and 100 and (b) the Bingham number for $Wi = 0.01, 0.1, 2$ and 16 .




Figure 5: Mean streamwise velocity profile u as a function of (a) the Bingham number for $Bi = 0.1, 2.8, 11.2$ and 100 at $Wi = 0.01$ and (b) the Weissenberg number for $Wi = 0.01, 0.1, 2$ and 16 at $Bi = 22.4$.

small to avoid the development of a turbulent flow and that no perturbations were added to the zero initial condition.

First, we consider the combined effects of the Bingham and the Weissenberg numbers on the frictional resistance of the flow quantified by the Fanning friction factor f , defined as $2\tau_w/\rho U_b^2$ being τ_w the total wall shear stress including both the viscous and elastoviscoplastic contributions. Figure 4(a) shows the Fanning friction factor f as a function of the Weissenberg number for various Bingham numbers. In particular, the cyan, brown, purple and green lines are used for $Bi = 0.1, 2.8, 11.2$ and 100 , respectively. The friction factor f decreases nearly linearly with Wi (in logscale). However, at $Bi = 0.1$ the factor f is constant, which is consistent with the viscoelastic flows in the laminar regime. Results clearly show that the elastic effects become more prominent with Bi , leading to a steeper decay with Wi .

Next, we consider the reverse case, where we study effects of Bingham number at a fixed Wi , as shown in figure 4(b). We find that f increases non-linearly with the Bingham number Bi , and that the dependency on Bi decreases with the Weissenberg number Wi .




Figure 6: Percentage of the unyielded volume Vol_s as a function of (a) the Weissenberg number for $Bi = 0.1, 2.8, 11.2$ and 100 and (b) the Bingham number for $Wi = 0.01, 0.1, 2$ and 16 .

The increase of f can be explained by subtle changes in the mean streamwise velocity profile. The non-dimensional streamwise velocity profile u/U_b is shown in figure 5(a) at $Wi = 0.01$ and $Bi = 0.1, 2.8, 11.2, 100$ as a function of the wall-normal distance y/h . It can be seen that the solid plug in the middle of the channel increases with the Bingham number. The plug moves with a uniform velocity, and its velocity decreases with Bi due to mass conservation, leading to an increase in the wall shear stress.

The variations of the non-dimensional mean velocity profile u/U_b at $Bi = 22.4$ with the Weissenberg number, see Figure 5(b), demonstrate that the solid plug in the middle of the channel decreases with Wi . Indeed, the total stress magnitude in a channel flow increases with elasticity, leading to earlier yielding (Chaparian & Tammisola 2019). To further quantify these observations, the volume of the solid region is shown in figure 6 for various combinations of Wi and Bi . The results are consistent with the observations in figure 4, since the solid volume Vol_s is proportional to the friction factor f .

3.2. Turbulent flow

We examine turbulent channel flows of an elastoviscoplastic fluid, together with the baseline Newtonian ($Bi = 0$ and $Wi \approx 0$), viscoelastic ($Bi = 0$) and almost viscoplastic ($Wi \approx 0$) cases. All simulations have been performed until statistically steady state (at least 500 nondimensional units). Hence in the turbulent flow cases, the turbulence is always fully developed. However, for some parameter values the flow is not turbulent, because it has laminarized by increasing elasticity or plasticity.

The flow rate is constant in all simulations, so that the flow Reynolds number based on the bulk velocity is fixed, i.e., $Re = \rho U_b h / \mu_0 = 2800$, where the bulk velocity U_b is the average value of the mean velocity computed across the whole domain and μ_0 is the total zero-shear viscosity. In the turbulent regime, this bulk Reynolds number corresponds to a nominal friction Reynolds number $Re_\tau = \rho u_\tau h / \mu_0 = 180$ for a Newtonian fluid, u_τ being the friction velocity. A wide range of elasticity and plasticity is investigated: the Weissenberg number $Wi = \lambda U_b / h$ is varied in the range $0 \leq Wi \leq 16$ to study the role of fluid elasticity, while the Bingham number $Bi = \tau_0 h / \mu_0 U_b$ is varied between 0 and 22.4. The viscosity ratio and the extensibility parameter are fixed to $\beta = \mu_f / \mu_0 = 0.9$ and $L^2 = 3600$.

The viscous units used above are indicated by the superscript $+$, and are built using




Figure 7: Combined effects of elasticity and plasticity. A flow regime map is shown by symbols: \square - turbulent, \blacksquare - laminar. Colorscale shows drag reduction compared to the Newtonian case. Top figure colorscale: $DR = [1 - (Re_\tau / Re_{\tau, Wi=0})^2] \times 100\%$. The colorscale spans ± 65 from red (drag reduction) to violet (drag increase). Bottom figure colorscale: $DR_2 = [1 - f_{EVP} / f_N] \times 100\%$ where f_{EVP} and f_N denote skin friction for EVP and Newtonian cases, respectively.

the friction velocity u_τ as the velocity scale and the viscous length $\delta_\nu = \nu / u_\tau$ as the length scale. Here, we define the friction velocity as

$$u_\tau = \sqrt{\left(\frac{1}{Re_b} \frac{d\bar{u}}{dy} + \bar{\tau}_{12} \right) \Big|_{y=0}}, \quad (3.1)$$




Figure 8: The shear effective viscosity μ_e for (a) VE, (b) VP and (c) EVP cases. (a) VE case: the green, magenta, black and blue colors are used for $Wi = 2, 4, 8$ and 16 . (b) VP case: the red, orange, cyan and violet colors are used for $Bi = 0, 0.28, 0.7$ and 1.4 , respectively (c) EVP case is at fixed $Wi = 4$ and the green, red and black colors are used for $Bi = 0, 2.8$ and 5.6 , respectively.

where we have taken into account also the elastoviscoplastic shear stress at the wall. Note that the actual value of the friction velocity in our simulations is computed from the friction coefficient, obtained with the driving streamwise pressure gradient, rather than from its definition.

We first discuss the qualitative flow characteristics for various combinations of Wi and Bi . A qualitative overview of the resulting flow regimes as functions of Wi and Bi is presented in figure 7.

The empty and filled symbols in figure 7 represent turbulent and laminar regimes, respectively. As expected, the flow becomes laminar and steady with an increasing Bingham number. The critical Bi_c can be defined as the lowest value of Bi where laminarisation occurs, at each Wi . At $Wi = 0.01$, the flow is near-viscoplastic and fully laminarises at the relatively low critical $Bi_c = 2.8$ (Rosti et al. 2018c)[†]. Laminarization of the viscoplastic flow with increasing Bingham number is closely related to the increase of the core unyielded region which grows from the centerline towards to the walls, and damps

[†] Note that results for viscoplastic cases used in this work are taken from our previous work Rosti et al. (2018c)

out turbulent fluctuations in the core. As described in Rosti *et al.* (2018c), the near-wall streaks were intensified and became more coherent. The low-speed streaks, usually associated with positive wall-normal fluctuations, reach higher wall-normal distances than the high-speed streaks, thus inducing the flow to yield at higher wall-normal distances if the local stress reaches the yield stress threshold. Indeed, the unyielded regions preferentially form above high-speed streaks. Overall, the flow becomes more and more correlated in the streamwise direction when increasing the Bingham number, with high levels of flow anisotropy close to the wall, similarly to what observed in other drag reducing flows. Differently from the other flows, however, both the streamwise and spanwise correlations grow with the Bingham number also away from the wall, due to the growth of the unyielded region.

As the flow becomes more elastic, the critical Bi_c shows a non-monotonic behaviour, first increases with Wi , then decreases. The reason for this non-monotonic behaviour is attributed to the fact that the coherent structures are highly influenced by the relative width of the plug compared to the yielded regions around it, as will be described later.

The colors in figure 7 represent a measure of drag reduction compared to a Newtonian fluid. The top figure shows $DR = [1 - (Re_\tau/Re_{\tau, Wi=0})^2] \times 100\%$. For flows in the turbulent regime, DR increases with Bi for all Wi studied in this work. In the laminar regime however, at low $Wi = 0.01$, the DR changes sign, showing drag increase, whereas for higher $Wi \geq 2$ values, the DR only slightly decreases with Bi . This is consistent with the results for the Fanning factor shown in figure 8. It is well known that a finite viscoelasticity reduces drag compared to a Newtonian flow, and this has been exploited in many previous studies and in the industry. The figure seems to show that a combination of finite Wi and Bi results in a much greater drag reduction than a finite Wi alone. However, a closer inspection shows that the very high drag reduction $DR > 70\%$ occurs when the flow laminarises, because we compare with the drag in the Newtonian flow in the turbulent regime. We wanted to eliminate the effect of laminarization on drag reduction, and also try to exclude the effects of shear-thinning. Therefore, in the bottom figure, we show another measure of drag reduction which excludes the influence of shear thinning (Housiadas & Beris 2003): $DR_2 = [1 - f_{EVP}/f_N] \times 100\%$, where f_{EVP} and f_N denote skin friction for EVP and Newtonian cases, respectively. Following Dean (1978):

$$f_N = \begin{cases} 12/Re_w & \text{laminar} \\ 0.073Re_w^{-0.25} & \text{turbulent,} \end{cases}$$

where $Re_w = \rho U 2h / \mu_w$ and $\mu_w = \tau_w / \dot{\gamma}_w$, and subscript w denotes wall quantities. Using DR_2 as a measure, the highest drag reduction is achieved either at high Wi , or in EVP flow when Wi and Bi are both moderate, in the same region where laminarization is delayed to higher Bi . In general, the drag reduction values remain very similar for these two measures in the turbulent regime, indicating that shear thinning has no major influence on drag reduction at the studied parameter values. Despite this, the viscosity profiles (figure 8) show shear-thinning for VE, EVP and VP cases. Apparently, plasticity plays a strong role on shear-thinning, as both VP and EVP show stronger shear-thinning. For the EVP case at $Wi=4$ and $Bi=5.6$, we are approaching results of VP at $Bi=1.4$, thus elasticity seems to decrease shear-thinning.

The main responsible for the non-monotonic trends is the unyielded region of the flow. The unyielded regions show a non-trivial and complex trend with Bi and Wi , with significant differences also between the laminar and turbulent regimes. In order to better understand the flow, we start by showing visualizations of the instantaneous distributions of the yielded and unyielded regions in figure 9. In particular, the figure

shows instantaneous cross-stream planes ($x - y$ plane) where the unyielded regions are colored in brown; in the yielded regions we report color contours of the spanwise vorticity, ω_z . At $Bi = 0$ and $Wi \approx 0$ we recognize the classic vorticity field of turbulent channel flows, with high vorticity levels at the walls, and the footprints of the classical turbulent streaky structures. As Wi increases, the flow becomes smoother, the flow structures seem to be more elongated and the streamwise coherency of the flow increases, as is typical of drag-reducing flows.

Note that although the turbulence activity is reducing with Wi , the purely viscoelastic flow does not laminarise. On the other hand, for every Wi , the flow returns to laminar for a sufficiently high Bingham number ($Bi > Bi_c$). In particular, we observe that as Bi increases, the amount of fluid which is unyielded grows, eventually forming a fully connected plug spanning the whole streamwise and spanwise lengths, thus leading to the decay of turbulence and the return to a fully laminar regime. However, at intermediate Wi , we observe that a higher Bi_c is required to laminarise the flow than at low or high Wi . At intermediate Wi , the equilibrium solutions indicate that the unyielded region is narrower than in the viscoplastic flow (Chaparian & Tammisola 2019), and we propose that this allows instabilities to be sustained in the yielded regions. In the present simulation at intermediate Wi , a plug was formed initially and the flow seemed to laminarise, but soon a large-scale roll-up motion developed at the edges of the unyielded region, recreating the unsteadiness and turbulence. On the other hand, at higher values ($Wi > 4$) this effect does not occur thus leading to lower Bi_c . This phenomenon could be attributed to the fact that the unyielded region becomes too thin to create any instability. Moreover, the yielded region becomes smoother at high Wi enhancing laminarisation.

It is not obvious what drives the instability leading to the roll-up motion, because the laminar flow profile is not inflectional. A sharp viscosity contrast can lead instabilities in channel and shear flows. The unyielded region could play a similar role as a high-viscosity fluid in the centre of the channel, a configuration which can be unstable at high Reynolds numbers (Hooper & Boyd 1987; Govindarajan & Sahu 2013). On the other hand, a channel flow of Bingham fluid is known to be linearly stable at all Reynolds numbers. Although the linear stability of EVP flow has not been studied, the transition that we observe could be subcritical, like for Bingham fluids. However, the roll-up structure we observe does not resemble the optimal non-modal instabilities in Bingham fluid: streamwise-travelling waves (Nouar *et al.* 2007) or oblique waves (Nouar & Bottaro 2010).

For laminar flows ($Bi > Bi_c$), a further increase of Bi leads to a growth of the unyielded region, which induces an increase of the wall shear stress and a consequent drag increase, as previously observed in figure 8. This is different from observations in the turbulent regime, where the drag reduces with both Wi and Bi (Rosti *et al.* 2018c).

3.3. Flow statistics

Here, we discuss the turbulent statistics for elastoviscoplastic flows. To facilitate comparisons, we provide results for the two limiting cases: near-viscoplastic and viscoelastic flows, and then compare these to the flows with finite elasticity and plasticity. The near-viscoplastic flow was presented in our earlier work (Rosti *et al.* 2018c), and was computed using the Saramito model at $Wi = 0.01$, $\beta = 0.95$, and varying Bi . The viscoelastic flow is computed at varied Weissenberg number $0 \leq Wi \leq 16$ and fixed Bingham number $Bi = 0$, and the FENE-P model parameters are $\beta = 0.9$ and $L^2 = 3600$, unless indicated otherwise.

We first discuss the mean streamwise velocity profiles in relation to drag reduction




Figure 9: Contours of the instantaneous spanwise vorticity $-\omega_z$ in a $x - y$ plane As a function of the Bingham and Weissenberg numbers. Color scales ranges from $-3U_b/h$ (blue) to $3U_b/h$ (red). The brown areas represent the instantaneous regions where the flow is not yielded.




Figure 10: Mean streamwise velocity profile \bar{u} as a function of the wall-normal distance y in wall units. (a) Near-viscoplastic flow ($Wi = 0.01$) (b) Viscoelastic flow ($Bi = 0$). The dashed line and symbols in the figure correspond to the Virk curve at MDR (Virk 1975) and the results of Kim *et al.* (1987), respectively.

shown in figure 7. In figure 10, the velocity profiles are shown in wall units. The profiles for viscoplastic flow in figure 10(a) are similar to the Newtonian case for $Bi < 1.4$. For $Bi = 1.4$, the difference becomes more significant with zero shear region at the centerline. At $Bi = 2.8$, the flow becomes laminar with a large zero-shear region, leading to drag increase as observed in figure 7. We can observe that the flow remains unyielded mostly in the logarithmic and outer layer, while it is always yielded in the viscous sublayer.

For viscoelastic flows, $DR\%$ increases monotonically with Wi in the range of $Wi =$




Figure 11: Elastoviscoplastic flow: (a) drag reduction as a function of Bi and (b) mean streamwise velocity profile \bar{u} as a function of the wall-normal distance y in wall units. The Weissenberg number Wi and the extensibility parameter L^2 are fixed and equal to 4 and 3600, respectively (FENE-P model).

$\mathcal{O}(1)$ and start to saturate at $Wi > 10$. The maximum drag reduction is close to 40% at $Wi = 16$. Figure 10(b) shows the mean streamwise velocity profiles in wall units. It can be seen that increasing Wi the velocity profiles collapse in the viscous sublayer, however, shift upward in the buffer region (thickening of the buffer layer) and are parallel to the Newtonian profile. Note that we do not reach the Virk’s maximum drag reduction (MDR) asymptote (Virk 1975), which is out of scope of the present study. The shift in the velocity profile is consistent with results in literature (Xi & Graham 2010; Shahmardi et al. 2019).

We next consider the elastoviscoplastic flow. The drag reduction values and the corresponding mean streamwise velocity profiles for $Wi = 4, \beta = 0.9, L^2 = 3600$ and $Bi = 0, 2.8, 5.6, 11.2$ and 22.4 are shown in figure 11. Similarly to the viscoplastic flow, the $DR\%$ increases with Bi in the turbulent regime. Unlike pure viscoelastic case, plasticity enhances the DR going from LDR ($DR \lesssim 40$) at $0 \leq Bi < 5.6$ to HDR ($40 < DR \lesssim 60$) at $Bi = 5.6$. Moreover, the laminar regime delays to larger $Bi > 5.6$, which may be attributed to the dramatic effects due to the polymer dynamics. Unlike the viscoplastic case, $DR\%$ only slightly decreases in the laminar case as shown also earlier in figure 7. The change of mean streamwise velocity profile with Bi is more significant than in figure 10(a) and more similar to figure 10(b) for $Bi \leq 5.6$, i.e., the velocity profile collapse in the viscous sublayer, and shift upward in the buffer and log-law layer approaching the Virk’s asymptote. In contrast, for $Bi > 5.6$ the flow fully laminarises and becomes similar to the case in figure 10(a), with zero-shear region at the centerline.

Next, we analyze the wall-normal distribution of the Reynolds stress components $\overline{u'u'}$ and $\overline{v'v'}$, shown in figure 12 together with the Newtonian case by Kim et al. (1987) (blue symbol). The profiles are normalized with u_τ^2 . The results for the viscoelastic case (top row) show that the $\overline{u'u'}$ increases while $\overline{v'v'}$ decreases with Wi . In general, the shape of the profiles is similar to the corresponding Newtonian one, but the magnitude changes with Wi . Moreover, all the peaks move towards the channel center in agreement with the thickening of the buffer layer observed in the mean velocity profile. A similar behaviour has been noticed in the literature for drag reducing turbulent viscoelastic flows (White & Mungal 2008; Dallas et al. 2010). The VP case ($Wi = 0.01$) is depicted in the middle row to examine the effects of the Bingham number in the range $0 \leq Bi \leq 2.8$. We




Figure 12: Wall-normal profiles of components of the Reynolds stress tensor, normalized with u_τ^2 . The first column shows $u'u'$, the second column $v'v'$. Top row: VE flow at various Wi and fixed $Bi = 0$. Middle row: VP flow at various Bi and fixed $Wi = 0.01$. Bottom row: EVP flow at various Bi and fixed $Wi = 4$. The extensibility parameter L^2 is fixed and equals to 3600. The \bullet symbols indicate the DNS data of Kim et al. (1987).

clearly observe that the peak of the streamwise component $\overline{u'u'}$ increases with Bi , while it decreases for $\overline{v'v'}$. A similar trend is observed for the EVP case ($Wi = 4$) as depicted in the bottom row.

Although the overall trends are similar, the combined effects of elasticity and plasticity




Figure 13: Wall-normal profiles of components of the Reynolds stress tensor, normalized with u_τ^2 . The first column shows $w'w'$, the second column $u'v'$. Top row: VE flow at various Wi and fixed $Bi = 0$. Middle row: VP flow at various Bi and fixed $Wi = 0.01$. Bottom row: EVP flow at various Bi and fixed $Wi = 4$. The extensibility parameter L^2 is fixed and equals to 3600. The \bullet symbols indicate the DNS data of Kim et al. (1987).

in the EVP flows result in larger deviations from the Newtonian flow than for the two limiting cases, particularly for the peak in the $u'v'$ profile. It is also interesting to note that in the EVP flow the peak moves non-monotonically, unlike in the VE and VP cases: it first moves away from the wall as Bi increases ($Bi \leq 5.6$), and then moves slightly




Figure 14: Probability of the fluid to be unyielded P_s in: (a) VP flow at $Wi = 0.01$ and EVP cases at (b) $Wi = 4$ and (c) $Wi = 8$. The percentage of the unyielded volume Vol_s are presented in the legends. For (a) VP case, the red, orange, cyan, violet and green colors are used for $Bi = 0, 0.28, 0.7, 1.4$ and 2.8 , respectively. For (b & c) EVP cases, green, red, black and orange colors are used for $Bi = 0, 2.8, 5.6$ and 11.2 , respectively. The extensibility parameter for the EVP cases is $L^2 = 3600$.

back towards the wall. The stress components $\overline{u'v'}$ and $\overline{w'w'}$ show similar trends as $\overline{v'v'}$, and are shown in figure 13 for completeness.

Figure 14 shows P_s , the probability of the fluid to be unyielded in a given vertical position, and Vol_s , the percentage of the volume that was unyielded on average, for VP ($Wi = 0.01$) and EVP ($Wi = 4$ & 8) cases. The probability P_s is displayed against the wall-normal distance y , whereas the volume percentage is depicted in the legend. The probability P_s ranges from 0 (always fluid) to 1 (always elastic solid).

For the laminar case, as expected, P_s sharply changes along the interface between the unyielded and yielded region. For turbulent cases, the probability P_s increases smoothly across the channel with a maximum in the vicinity of the centerline and a minimum near the wall. This happens due to the time-dependent nature of the turbulent flow.

For the VP case, P_s and Vol_s increase with Bi , reaching the maximum ($Vol_s = 54\%$) at $Bi = 2.8$, when the flow is fully laminar. The volume of the unyielded region further increases when Bi increases in the laminar regime, as illustrated in figure 5 (a). Let us now consider the EVP cases. A careful inspection of figure 14 reveals that the unyielded




Figure 15: Mean polymer extension in: (a) VE ($Bi = 0$), (b) VP ($Wi = 0.01$), EVP for (c) $Wi = 4$ and (d) $Wi = 8$. The undeformed polymer stretching ($\sqrt{Tr(\mathbf{I})}/L$ and $\sqrt{Tr(\mathbf{I})}$) is represented by the black dashed line. The extensibility parameter is $L^2 = 3600$.

volume Vol_s is smaller in EVP flows than in VP flows, in both laminar and turbulent states. Also, Vol_s further decreases as Wi increases, from 30% at $Wi = 4$ to 26% at $Wi = 8$, as seen in figure 14(b) and (c). The reason is that the elastic stress in channel flows increases with Wi , resulting in a smaller unyielded volume. Moreover, the Vol_s increases monotonically with Bi also for the EVP case, as long as $Bi < Bi_c$. However, when the flow laminarises ($Bi \geq Bi_c$), Vol_s decreases owing to a narrow plug region. An explanation to the decrease can be found by comparing the laminar and turbulent mean flow profiles. In laminar VE channel flows, the elastic stress is known to be proportional to both the local shear and Wi , and therefore, the elastic stress forms the largest part of the total stress at moderate Wi . In laminar flows, the shear is finite almost everywhere across the channel. In turbulent flows, however, the mean flow shear is small in the central region, and hence the elastic stresses are smaller on average, with the Reynolds stresses becoming more important in yielding the material.

We now present the statistics of the polymer conformation tensor for VE, VP and EVP cases. The mean profiles of the polymer stretching $\sqrt{Tr(\mathbf{C})}/L$ are shown in Figure 15(a) for the VE case at $Wi = 2, 4, 8$ and 16, where the dashed line in the figure indicates the case of coiled polymers (conformation tensor equal to identity). As expected, the polymer stretching increases monotonically with the Weissenberg number Wi . The mean polymer

stretching first increases with maximum in the vicinity of the wall, then decreases with minimum at the center. The observed near-wall peak is mostly due to the interaction between polymers and near-wall vortices (Xi & Graham 2010; Dubief et al. 2013). Viscoelastic effects become more prominent throughout the domain when increasing Wi and the peak values move away from the wall.

The mean polymer extension for the VP cases at $0 \leq Bi \leq 2.8$ is shown in figure 15(b). For $Bi \lesssim 2$, corresponding to the turbulent regime, the stress profile is nearly constant except in the near wall region where it is maximum. Note that for the laminar case, the stress monotonically decreases along the wall normal direction. Finally, the results pertaining the EVP flows at $0 \leq Bi \leq 11.2$ and $Wi = 4$ & 8 are presented in figure 15(c) and (d). For the turbulent EVP cases ($Bi < 11.2$), the stress profiles are qualitatively similar to the VE ones. The maximum values are in the vicinity of the wall and the minimum at the centerline ($y = h$). Moreover, the minimum values increase with Bi while peaks are not sensitive to Bi at $Bi < Bi_c$. For the laminar flows, the profile is qualitatively similar to the viscoplastic one, with maximum and minimum values at the wall and centerline, respectively.

3.4. Energy and stress balance

To further characterise the flow, we study the energy and shear stress budget for the viscoelastic and EVP cases. We first consider how the energy stress budgets evolve with Weissenberg number, at zero Bingham number.

An overall view of the velocity fluctuations is obtained from the turbulent kinetic energy $\mathcal{K} = (u'^2 + v'^2 + w'^2)/2$, normalized with u_τ^2 (figure 16(a)). Following Dallas et al. (2010), the budget of turbulent kinetic energy integrated over the whole domain can be written as follows:

$$\int_{\mathcal{V}} \mathcal{P} d\mathcal{V} = \int_{\mathcal{V}} \varepsilon d\mathcal{V} + \int_{\mathcal{V}} \Pi d\mathcal{V}, \quad (3.2)$$

where \mathcal{V} is the volume of the domain, $\mathcal{P} = -\overline{\rho u'v'} d\bar{u}/dy$ is the turbulent production, $\varepsilon = \mu \overline{\partial u'_i/\partial x_j \partial u'_i/\partial x_j}$ is the turbulent dissipation and $\Pi = \overline{\partial u'_i/\partial x_j \tau'_{ij}}$ is the dissipation due to the polymers.

The turbulent kinetic energy increases with Wi , and its profile is similar to the streamwise velocity fluctuation in figure 12(a), as the streamwise velocity is of larger magnitude than the other velocity components. On the other hand, the turbulent production by the Reynolds shear stress $\mathcal{P} = -\overline{u'v'} d\bar{u}/dy$ is continuously reduced when increasing Wi . The peak values occur in the buffer layer, moving towards the channel center with increased DR consisted with thickening of the buffer layer. We also computed the turbulent dissipation $\varepsilon = \mu \overline{\partial u'_i/\partial x_j \partial u'_i/\partial x_j}$ of the fluctuating velocity field u'_i . The dissipation ε also attenuates with Wi , while the profile maintains its shape with maximum value at the wall and minimum at the centerline. Volume averaged quantities of $\int \mathcal{P} dy$, $\int \varepsilon dy$ and dissipation due to polymers $\int \Pi dy$ are shown in figure 16(d). It can be seen that the average turbulent production and viscous dissipation decrease with Wi , while the polymeric dissipation increases with Wi . The decrease in \mathcal{P} and ε with Wi is consistent with the observed drag reduction. Note that Π first increases with Wi , but slightly decreases at $Wi = 16$, which could be due to the fact that we are approaching the HDR regime. Dallas et al. (2010) observed a similar non-monotonic trend with Wi for Π *i.e.*, the polymeric dissipation increases in LDR while it decreases in HDR and MDR. Overall, our viscoelastic results are in agreement with the literature for turbulent flow with polymer additives (Warholic et al. 1999; Xi & Graham 2010; Dallas et al. 2010).

Next, we show the mean viscous ($\bar{\tau}_V$) and viscoelastic stress ($\bar{\tau}_E$) profiles as a function




Figure 16: VE case: Wall-normal profiles of (a) the turbulent kinetic energy $\mathcal{K} = (u'^2 + v'^2 + w'^2)/2$ and of (b) the turbulent production $\mathcal{P} = -\rho u'v' d\bar{u}/dy$, (c) the turbulent dissipation $\varepsilon = \mu \partial u'_i/\partial x_j \partial u'_i/\partial x_j$ and (d) average contributions to the energy balance from \mathcal{P} , ε and dissipation due to the polymers $\Pi = \partial u'_i/\partial x_j \tau'_{ij}$, all normalized with the friction velocity u_τ^3 . The symbols in the figure correspond to results of Kim *et al.* (1987) for the Newtonian case.

of the Weissenberg number, see figure 17. The viscous stress profiles coincide close to the wall and in the vicinity of the channel core but increase slightly in the buffer layer. The viscoelastic stress profile has a peak in the vicinity of the wall and minimum in the center. The $\bar{\tau}_E$ changes non-monotonically, it first increases reaching maximum in the buffer layer and then decreases reaching a minimum at the centerline. With increase in Wi the peak moves towards the core region.

To gain further understanding, the shear stress budget is shown in figure 18 for the VE cases with $Wi = 2$ and $Wi = 16$, normalized with the corresponding wall stress. The total shear stress $\bar{\tau}_T$ can be written as $\bar{\tau}_T = \bar{\tau}_V + \bar{\tau}_E + \bar{\tau}_R = (1 - y/h)\tau_w$ where the viscous stress $\bar{\tau}_V = \mu d\bar{u}/dy$, the Reynolds stress $\bar{\tau}_R = -\rho u'v'$ and viscoelastic stress $\bar{\tau}_E$ tensor. Note that unlike the Newtonian case, the total wall shear stress is sum of the viscous and viscoelastic contributions. For $Wi = 2$, the behavior is similar to the Newtonian case with the viscous stress dominating close to the wall and the Reynolds stress in the core. The viscoelastic effects become more pronounced at $Wi = 16$, in that the viscous and viscoelastic stresses increase, while the Reynolds stresses diminish.




Figure 17: VE case: Shear component of the mean (a) viscous stress $\bar{\tau}_V$ and (b) viscoelastic stress tensor $\bar{\tau}_E$ as a function of the wall-normal distance y . The extensibility parameter L^2 is fixed and equals to 3600.




Figure 18: VE case: Normalised shear stress balance across the channel, for (a) $Wi = 2$ and (b) $Wi = 16$. The total shear stress varies linearly across the channel height.

Finally, we perform the same energy and momentum budget analysis to consider the combined effects of elasticity and plasticity. The energy budget is shown in figure 19 at fixed Weissenberg number $Wi = 4$, while varying the Bingham number in the range $0 \leq Bi \leq 11.2$. Qualitatively, the effect of Bingham number on the energy budget is similar to the viscoplastic case in Rosti *et al.* (2018a), the peak of \mathcal{K} increases with Bi , while the peak values for \mathcal{P} and ε decrease. The volume-averaged viscous dissipation decreases, while EVP dissipation increases with Bi . Surprisingly however, the turbulent production slightly increases with Bi at this finite Weissenberg number, in contrast with the viscoplastic flow. The shear components of the mean viscous and EVP stress tensors are shown in figure 20. In viscoplastic flows, we observed that the shear component of the EVP stress tensor increased everywhere across the channel. In the combined case however (figure 20(b)), its value at the wall remains constant in the turbulent regime. In the laminar regime, as expected, the shear component changes linearly in the liquid region and is zero in the solid region. The EVP stress continuously increases with Bi towards the center of channel. Finally, we report in figure 21 the shear stress budget for




Figure 19: EVP case: Wall-normal profiles of (a) the turbulent kinetic energy $\mathcal{K} = (u'^2 + v'^2 + w'^2)/2$ and of (b) the turbulent production $\mathcal{P} = -\rho u'v' d\bar{u}/dy$, (c) the turbulent dissipation $\varepsilon = \mu \overline{\partial u'_i/\partial x_j \partial u'_i/\partial x_j}$ and (d) average contributions to the energy balance due to \mathcal{P} , ε and dissipation due to fluctuation of the EVP stresses $\Pi = \overline{\partial u'_i/\partial x_j \tau'_{ij}}$, all normalized with the friction velocity u_τ . The Weissenberg number Wi and the extensibility parameter L^2 are fixed and equal to 4 and 3600, respectively (FENE-P model). The symbols in the figure correspond to results of Kim et al. (1987) for the Newtonian case.

the cases with $Bi = 0$ and $Bi = 5.6$, normalized with the corresponding wall stress. With increasing Bi , the EVP and viscous stresses grow more across the channel, further reducing the Reynolds stresses, and hence the combined case deviates even more from the Newtonian flow than the viscoelastic case does.

3.5. Intermittent dynamics

Finally, we compare the intermittent dynamics for purely viscoelastic, viscoplastic and elastoviscoplastic cases. Previously Xi & Graham (2010, 2012b) observed two distinct time intervals, denoted as hibernating and active, for viscoelastic turbulent flow in minimal channel geometry. During the hibernating intervals, drag reduction is high and turbulence is partly attenuated, whereas the active intervals represent active turbulence similar to the Newtonian turbulent flow.

Figure 22(a) shows the time evolution of the friction Reynolds number Re_τ for the viscoelastic flow. We choose five time instants (i–v) defined in figure 22(a): (iii) is in the




Figure 20: EVP case: Shear component of the mean (a) viscous stress $\bar{\tau}_V$ and (b) elasto-viscoplastic stress tensor $\bar{\tau}_E$ as a function of the wall-normal distance y . The Weissenberg number Wi and the extensibility parameter L^2 are fixed and equals to 4 and 3600, respectively (FENE-P model).




Figure 21: EVP case: Normalised shear stress balance across the channel, for (a) $Bi = 0$ and (b) $Bi = 5.6$. The total shear stress varies linearly across the channel height. The Weissenberg number Wi and the extensibility parameter L^2 are fixed and equals to 4 and 3600, respectively (FENE-P model).

active regime, whereas (i and v) are in the hibernation regime. The instantaneous velocity profiles at these times are shown in figure 22(b). Note that velocity profiles are shown in inner units based on the instantaneous friction velocity. For convenience, data for the Newtonian case (Kim et al. 1987), represented by blue symbols, is also shown. As expected from previous work mentioned above, the profile changes between the Newtonian and the Virk profile, approaching the latter one at the lowest Re_τ (instant v).

The time evolution of the friction Reynolds number for the viscoplastic flow is shown in figure 22(c). Viscoplastic flow does not hibernate, so we choose four time instants in the turbulent regime. A more limited range of friction Reynolds numbers is observed, i.e. $165 < Re_\tau < 185$. Indeed, the instantaneous velocity profile figure 22(d) at the chosen times only slightly deviates from the Newtonian flow, represented by blue symbols in the figure.




Figure 22: Time series for hibernation phenomenon. Re_τ evolution and mean streamwise velocity profile \bar{u} at time instants $i-v$ defined in (a), (c) and (e) for VE, VP and EVP, respectively. The parameters are: $Wi = 16$ and $Bi = 0$ for VE flow, $Wi = 8$ and $Bi = 2.8$ for EVP flow, and $Wi = 0.01$ and $Bi = 1.4$ for VP flow.

Let us now consider the EVP flow where both elastic and plastic effects are significant. It is remarkable to see that the EVP flow (figure 22(e)) behaves like the VE flow, with significant drag reduction in the hibernation regime. Interestingly, the elastic characteristics of the intermittent turbulent dynamics are even stronger for the EVP flow than for the VE flow as also observed in the velocity profiles. The profiles near the active regime




Figure 23: Hibernation phenomenon of VE and EVP fluids, at the same time instants as in figure 22. Mean polymer extension, wall normal \bar{C}_{22} and shear \bar{C}_{12} components of the mean conformation tensor for VE ($Wi = 16$ and $Bi = 0$, left column) and EVP ($Wi = 8$ and $Bi = 2.8$, right column) cases.

(instants i and v) are similar to LDR profiles, whereas the ones under hibernation are more like a HDR, with instant (iv) being very close to the Virk profile. Correspondingly, since the EVP flow hibernates longer periods, we observe a more significant drag reduction ($27\% < DR < 58\%$) than for the purely viscoelastic flow. It is worth noting that we




Figure 24: Probability of the fluid to be unyielded in EVP flow ($Wi = 8$ and $Bi = 2.8$), at the same time instants as in figures 22 and 23.

observed and compared several hibernation cycles in VE and EVP flows, in addition to the ones shown in the figure.

We also examine the instantaneous profiles of the mean polymer extension, wall normal and shear components of the conformation tensor for VE and EVP flow in figure 23. The polymer extension is maximal in the active regime (black and red lines), while it is minimal in the hibernation phase (orange and green lines). The same was observed in viscoelastic turbulent flow in minimal channel (Xi & Graham 2010, 2012b). While the qualitative picture is the same for VE and EVP, they do present some differences. It appears that at hibernation, the EVP flow has larger polymer extension and higher values of the wall-normal component than the VE flow, while the shear component of the EVP flow is lower, which explains drag reduction. On the other hand, the VE flow presents higher values of both components in the active turbulence regime[†]. EVP stresses are lowest in the hibernation state, and consequently, the probability P_s of the fluid to be unyielded is highest in the hibernation state, as shown in figure 24. The P_s -curves neatly divide into two distinct groups in active vs hibernating state, as characterised by Re_τ , and also by the wall-normal component of the conformation tensor C_{22} .

4. Flow structures

The elastoviscoplastic character of the flow affects the near-wall turbulent structures, and this is visually confirmed in figure 25. In the figure we identify the low- (blue) and high-speed (red) near-wall streaks with isosurfaces of the streamwise velocity fluctuations u' corresponding to the levels $u'^+ = \pm 0.25U_b$ for the values of Bi and Wi pertaining all the turbulent cases we have studied. In the Newtonian case ($Bi = 0$ and $Wi = 0$), we recognize in the shape of the streamwise velocity fluctuations the typical footprints of the near-wall streaks and quasi-streamwise vortices that characterize the near-wall turbulence and that are responsible for the wall-cycle that can sustain turbulence in classical wall-bounded flows (Jiménez & Pinelli 1999). In VE flows (the leftmost column in figure 25), as the elasticity increases, the low- and high speed streaks become less fragmented, are correlated over longer distances in the streamwise direction and grow

[†] We recognise that these profiles are only snapshots and may not represent accurately the whole dynamics




Figure 25: Isosurfaces of instantaneous streamwise velocity fluctuation u' for different Bingham and Weissenberg numbers. The flow goes from left to right and the color scale ranges from $-0.25U_b$ (blue) to $0.25U_b$ (red). The green planes in all the figures represent the rigid wall.

in size. This behaviour has been recognised in the past by several authors (Warholic et al. 1999; Escudier et al. 2009; Shahmardi et al. 2019; Le Clainche et al. 2020) who consistently reported that the inclusion of the polymers in the flow strongly modifies the near-wall structures, by overall enhancing the streamwise coherence of the flow and by increasing the size of the low- and high-speed streaks, thus also moving the quasi-streamwise vortices away from the wall.

A similar modification of the near-wall structures was found by Rosti et al. (2018c) for the near-viscoplastic case with $Wi \approx 0$ when increasing the Bingham number. Indeed, the figure clearly shows that the structures in the buffer layer are less fragmented and more elongated in the streamwise direction, as the Bingham number increases. Increase in Wi and Bi both result in the growth in size of the larger scale structures, which is consistent with an attenuation of the small-scale features of the flow and the consequent reduction of the turbulent dissipation previously observed. This results in a reduction of the friction Reynolds number Re_τ , i.e., drag reduction, similarly to what observed in other drag reducing flows, such as riblets and anisotropic porous walls (Choi et al. 1993; Rosti et al. 2018b). Although the modifications of the flow structures with Wi and Bi are similar, some differences are present. Indeed, plasticity alone in VP flows reduces the wall-normal fluctuations less than elasticity because the hibernating turbulent phases are reduced; this results in stronger ejection events and in turbulent structures that penetrate deeper in the bulk of the channel for high values of Bi . This difference is related to the presence of the unyielded region in the plastic cases, which is inherently intermittent and induces larger values of EVP dissipation rates Π than in the viscoelastic cases (figures 16(d) and 19(d)). Because of this, the drag reduction due to the plasticity is able to laminarise the flow while the one of elasticity is not. The two effects mix in a non-trivial way when both finite elasticity and plasticity are considered. In the EVP cases, the flow structures continue to become less fragmented and more streamwise coherent, with their

wall-normal size depending on the relative magnitude of Wi and Bi . Indeed, as also shown in figure 9, the unyielded region shows a complex trend with Wi and Bi , and this might influence the size of the flow structures. The flow always laminarizes at high enough Bingham numbers. However, the VP flow is laminar at $Bi > 2.8$, showing purely plastic turbulence, while the EVP flow at $Wi = 2$ becomes laminar only at $Bi > 5.6$, and hence the turbulence shows combined elastic and plastic characteristics. At high Wi ($Wi = 16$), the trend is reversed and the flow laminarizes again at $Bi = 2.8$, and the effect of plasticity on the turbulent viscoelastic flow is not large due to an early relaminarisation. This non-monotonic trend can be observed in figure 7.




Figure 26: $x - z$ planes at $y = 0.15h$ showing contours of the polymer extension $\sqrt{Tr(\overline{C})}/L$ (the colorscale goes from black to white). The blue and red isolines shows the streamwise velocity fluctuations $\pm 0.25U_b$. The top row shows cases with increasing $Wi = 2, 4, 8$ and 16 from left to right at fixed $Bi = 0$, while the bottom row cases with increasing $Bi = 0, 2.8$ and 5.6 at fixed $Wi = 2$. In the figures, the flow is from bottom to top.

The different effect of elasticity and plasticity on the turbulent flow can be better appreciated in figure 26 where we show wall-parallel contours of the instantaneous polymer extension $\sqrt{Tr(\overline{C})}/L$ at $y \approx 0.15h$, together with the footprints of the low- and high speed streamwise velocity streaks on the plane. In the top row of the figure we consider the viscoelastic cases with $Bi = 0$ and growing Weissenberg number Wi from 2 to 16. The figure confirms that as Wi grows, the polymer extension is enhanced, resulting in more

elongated and streamwise coherent structures. Also, it is evident from the figure that the flow structures grow in size, especially the low-speed ones. The second row depicts the results for a fixed Weissenberg number ($Wi = 2$) and growing Bingham number from 0 to 5.6. Again, we note that as Bi increases in the EVP flow, the flow becomes more ordered and streamwise coherent, however from the figure we can also appreciate the different effect of elasticity and plasticity on the EVP flow: plasticity reduces the turbulent dissipation and the fragmentation of the turbulent structures, acting on both the low- and high-speed streaks equally. Indeed, both appear more elongated in the streamwise direction as Bi increases, with only a small growth in their spanwise dimension. On the other hand, elasticity affects mostly the low-speed streaks, while the high-speed ones remain fragmented despite growing in size. A common feature between the two flows is the tendency of the low-speed streaks to appear in regions where the polymers are highly elongated, while the high-speed streaks mostly appear in regions where polymers are not stretched.

5. Conclusions

The combined effect of finite Weissenberg and Bingham numbers in elastoviscoplastic flows has been investigated by direct numerical simulations in this work, and compared to the two limiting cases of VE and VP flows, where VP refers to the near-viscoplastic limit ($Wi = 0.01$) analysed in our previous work Rosti *et al.* (2018a). We study both laminar and turbulent flows, where the turbulent case has $Re_\tau = 180$ in the Newtonian limit. A wide range of Weissenberg and Bingham numbers is investigated in this work: $Wi = 0 - 16$ and $Bi = 0 - 24$.

Previously, we observed that the VP flow has a moderate drag reduction compared to Newtonian flow at intermediate Bingham numbers, while at higher Bingham numbers the flow relaminarises and drag increases. However, the EVP flow at finite Weissenberg numbers achieves higher drag reduction values, up to 70%, than both viscoplastic and viscoelastic flows at the same Re and Wi . Moreover, the drag of EVP flow keeps decreasing after relaminarisation at high Bingham numbers.

The VP flow became laminar at $Bi \geq 2.8$. The EVP flow is still turbulent at $Bi = 5.6$ at moderate Wi , but becomes laminar at $Bi = 5.6$ for higher Wi ($Wi \geq 8$). The moderate value of Wi triggers instabilities that reinstate turbulence, since the thickness of the unyielded central plug region is considerably reduced compared to the viscoplastic case. At higher Wi , the central plug region becomes too thin to create instabilities leading to laminarisation.

When analysing the flow statistics, the streamwise component of Reynolds stress tensor increases while the other components decrease compared to the Newtonian flow. This effect is seen for EVP, VE and VP flows. However, it is strongest for the EVP flow. At $Wi = 4$, $Bi = 5.6$ the components of the EVP flow deviate more from the Newtonian case than VE flow at $Wi = 16$, or any of the turbulent VP cases.

To characterise the intermittent dynamics relating to their drag reducing property of polymeric flows (Xi & Graham 2010, 2012b), we divided each flow into hibernating time intervals and periods of active turbulence. The VE flow at $Wi = 16.0$ and $Bi = 0$, EVP flow at $Wi = 8.0$ and $Bi = 2.8$ and VP flow at $Wi = 0.01$ and $Bi = 1.4$ were considered. The VP flow showed hibernation phenomenon with small drag reduction variation. However, the EVP flow hibernates more than any of the others, with the velocity profile reaching close to the Virk profile. All EVP stress components were highest in active turbulence and lowest in hibernation stages. The probability of the fluid to be

unyielded was clearly divided into two stages: low probability in active stages and high probability in hibernation.

Finally, we analysed the spatial flow structures and related them to the local elongation of the polymers. As previously noted, both elasticity and plasticity increase the streamwise coherence in the flow. In the EVP flows, we observed that polymer elongation increases with increasing Bingham number, again showing that elastic effects are stronger at finite Bingham numbers than in a purely elastic flow. In both VE and EVP flows, low-speed streaks appear in regions where polymers are more stretched, and high-speed streaks in regions where polymers are less stretched. However, plasticity in EVP flows reduces the turbulent dissipation and hence the fragmentation of both the low- and high-speed streaks equally, while in VE flows high-speed streaks remain fragmented.

Acknowledgment

D.I. and O.T. were supported by the European Research Council Grant no. ERC-2019-StG-852529, MUCUS, and by the Swedish Research Council grants No. VR2013-5789 and No. VR2017-0489. L.B. was supported by the European Research Council Grant no. ERC-2013-CoG-616186, TRITOS and by the Swedish Research Council Grant no. VR 2014-5001. L.B. and O.T. also acknowledge the support from the Swedish Research Council via the multidisciplinary research environment INTERFACE, Hybrid multiscale modelling of transport phenomena for energy efficient processes and the Grant No. 2016-06119. The authors acknowledge computer time provided by SNIC (Swedish National Infrastructure for Computing).

Conflict of interest

The authors report no conflict of interest.

REFERENCES

- ALGHALIBI, D., ROSTI, M. E. & BRANDT, L. 2019 Inertial migration of a deformable particle in pipe flow. *Physical Review Fluids* **4**, 104201.
- BALMFORTH, N J, FRIGAARD, I A & OVARLEZ, G 2014 Yielding to stress: recent developments in viscoplastic fluid mechanics. *Annual Review of Fluid Mechanics* **46**, 121–146.
- BENTRAD, H, ESMAEL, A, NOUAR, C, LEFEVRE, A & AIT-MESSAOUDENE, N 2017 Energy growth in hagen–poiseuille flow of herschel–bulkley fluid. *Journal of Non-Newtonian Fluid Mechanics* **241**, 43–59.
- BIANCOFIORE, L, BRANDT, L & ZAKI, T A 2017 Streak instability in viscoelastic Couette flow. *Physical Review Fluids* **2** (4), 043304.
- BINGHAM, EUGENE COOK 1922 *Fluidity and plasticity*, , vol. 2. McGraw-Hill.
- BRANDT, LUCA 2014 The lift-up effect: The linear mechanism behind transition and turbulence in shear flows. *European Journal of Mechanics - B/Fluids* **47**, 80 – 96, enok Palm Memorial Volume.
- CHAPARIAN, E. & TAMMISOLA, O. 2019 An adaptive finite element method for elastoviscoplastic fluid flows. *Journal of Non-Newtonian Fluid Mechanics* **271**, 104148.
- CHEDDADI, I, SARAMITO, P, DOLLET, B, RAUFASTE, C & GRANER, F 2011 Understanding and predicting viscous, elastic, plastic flows. *The European Physical Journal E* **34** (1), 1.
- CHOI, H, MOIN, P & KIM, J 1993 Direct numerical simulation of turbulent flow over riblets. *Journal of Fluid Mechanics* **255**, 503–539.
- CROCHET, M J & WALTERS, K 1983 Numerical methods in non-newtonian fluid mechanics. *Annual Review of Fluid Mechanics* **15** (1), 241–260.
- DALLAS, V., VASSILICOS, J. C. & HEWITT, G. F. 2010 Strong polymer-turbulence interactions in viscoelastic turbulent channel flow. *Phys. Rev. E* **82**, 066303.

- DE VITA, F, ROSTI, M E, IZBASSAROV, D, DUFFO, L, TAMMISOLA, O, HORMOZI, S & BRANDT, L 2018 Elastoviscoplastic flow in porous media. Journal of Non-Newtonian Fluid Mechanics **258**, 10–21.
- DEAN, R. B. 1978 Reynolds number dependence of skin friction and other bulk flow variables in two-dimensional rectangular duct flow. Journal of Fluids Engineering **100**, 215–223.
- DINGKREVE, M., FAZILATI, M., M., DENN, & BONN, D. 2018 Carbopol: from a simple to a thixotropic yield stress fluid. Journal of Rheology **62**, 773–780.
- DUBIEF, Y, TERRAPON, V E & SORIA, J 2013 On the mechanism of elasto-inertial turbulence. Physics of Fluids **25**, 110817.
- DUBIEF, Y, TERRAPON, V E, WHITE, C M, SHAQFEH, E S G, MOIN, P & LELE, S K 2005 New answers on the interaction between polymers and vortices in turbulent flows. Flow, Turbulence and Combustion **74** (4), 311–329.
- DUBIEF, Y, WHITE, C M, TERRAPON, V E, SHAQFEH, E S G, MOIN, P & LELE, S K 2004 On the coherent drag-reducing and turbulence-enhancing behaviour of polymers in wall flows. Journal of Fluid Mechanics **514**, 271–280.
- ESCUDIER, M P, NICKSON, A K & POOLE, R J 2009 Turbulent flow of viscoelastic shear-thinning liquids through a rectangular duct: Quantification of turbulence anisotropy. Journal of Non-Newtonian Fluid Mechanics **160** (1), 2–10.
- ESCUDIER, M P, POOLE, R J, PRESTI, F, DALES, C, NOUAR, C, DESAUBRY, C, GRAHAM, L & PULLUM, L 2005 Observations of asymmetrical flow behaviour in transitional pipe flow of yield-stress and other shear-thinning liquids. Journal of Non-Newtonian Fluid Mechanics **127** (2-3), 143–155.
- ESCUDIER, M P & PRESTI, F 1996 Pipe flow of a thixotropic liquid. Journal of Non-Newtonian Fluid Mechanics **62** (2-3), 291–306.
- ESMAEL, A. & NOUAR, C. 2008 Transitional flow of yield-stress fluids in a pipe: evidence of a robust coherent structure. Physical Review E **77**, 057302.
- FATTAL, R & KUPFERMAN, R 2004 Constitutive laws for the matrix-logarithm of the conformation tensor. Journal of Non-Newtonian Fluid Mechanics **123** (2), 281–285.
- FIROUZANIA, M., METZGER, B., OVARLEZ, G. & HORMOZI, S. 2018 The interaction of two spherical particles in simple-shear flows of yield-stress fluids. Journal of non-Newtonian Fluid Mechanics **255**, 19–38.
- FRAGGEDAKIS, D, DIMAKOPOULOS, Y & TSAMOPOULOS, J 2016 Yielding the yield-stress analysis: a study focused on the effects of elasticity on the settling of a single spherical particle in simple yield-stress fluids. Soft Matter **12** (24), 5378–5401.
- FRIGAARD, I. & NOUAR, C. 2003 On three-dimensional linear stability of poiseuille flow of bingham fluids. Physics of Fluids **15**, 2843–2851.
- FRIGAARD, I A, HOWISON, S D & SOBEY, I J 1994 On the stability of poiseuille flow of a Bingham fluid. Journal of Fluid Mechanics **263**, 133–150.
- GOVINDARAJAN, R. & SAHU, K. C. 2013 Instabilities in viscosity-stratified flow. Annual Review of Fluid Mechanics **46**, 331–353.
- GUANG, R, RUDMAN, M, CHRYSS, A, SLATTER, P & BHATTACHARYA, S 2011 A DNS investigation of the effect of yield stress for turbulent non-Newtonian suspension flow in open channels. Particulate Science and Technology **29** (3), 209–228.
- GUZEL, B, FRIGAARD, I & MARTINEZ, D M 2009 Predicting laminar–turbulent transition in Poiseuille pipe flow for non-Newtonian fluids. Chemical Engineering Science **64** (2), 254–264.
- HANKS, R W 1963 The laminar-turbulent transition for flow in pipes, concentric annuli, and parallel plates. AIChE Journal **9** (1), 45–48.
- HANKS, R W 1967 On the flow of Bingham plastic slurries in pipes and between parallel plates. Society of Petroleum Engineers Journal **7** (04), 342–346.
- HERSCHEL, WH & BULKLEY, R 1926 Measurement of consistency as applied to rubber-benzene solutions. In Am. Soc. Test Proc., vol. 26, pp. 621–633.
- HOLENBERG, Y, LAVRENTEVA, O M, SHAVIT, U & NIR, A 2012 Particle tracking velocimetry and particle image velocimetry study of the slow motion of rough and smooth solid spheres in a yield-stress fluid. Physical Review E **86** (6), 066301.
- HOOPER, A. P. & BOYD, W. G. C. 1987 Shear-flow instability due to a wall and viscosity discontinuity at the interface. Journal of Fluid Mechanics **179**, 201–225.

- HOUSIADAS, K. D. & BERIS, A. N. 2003 Polymer-induced drag reduction: Effects of the variations in elasticity and inertia in turbulent viscoelastic channel flow. *Physics of Fluids* **15**, 2369–2384.
- HULSEN, M A, FATTAL, R & KUPFERMAN, R 2005 Flow of viscoelastic fluids past a cylinder at high weissenberg number: stabilized simulations using matrix logarithms. *Journal of Non-Newtonian Fluid Mechanics* **127** (1), 27–39.
- IZBASSAROV, D & MURADOGLU, M 2015 A front-tracking method for computational modeling of viscoelastic two-phase flow systems. *Journal of Non-Newtonian Fluid Mechanics* **223**, 122–140.
- IZBASSAROV, D, ROSTI, M E, NIAZI ARDEKANI, M, SARABIAN, M, HORMOZI, S, BRANDT, L & TAMMISOLA, O 2018 Computational modeling of multiphase viscoelastic and elastoviscoplastic flows. *International Journal for Numerical Methods in Fluids* **88**, 521–543.
- JIMÉNEZ, J & PINELLI, A 1999 The autonomous cycle of near-wall turbulence. *Journal of Fluid Mechanics* **389**, 335359.
- KIM, J & MOIN, P 1985 Application of a fractional-step method to incompressible navier-stokes equations. *Journal of Computational Physics* **59** (2), 308–323.
- KIM, J, MOIN, P & MOSER, R 1987 Turbulence statistics in fully developed channel flow at low Reynolds number. *Journal of Fluid Mechanics* **177**, 133–166.
- LE CLAINCHE, S., IZBASSAROV, D., ROSTI, M., BRANDT, L. & TAMMISOLA, O. 2020 Coherent structures in the turbulent channel flow of an elastoviscoplastic fluid. *Journal of Fluid Mechanics* **888**, A5.
- MALEKI, A & HORMOZI, S 2017 Submerged jet shearing of visco-plastic sludge. *Journal of Non-Newtonian Fluid Mechanics* .
- METIVIER, C, NOUAR, C & BRANCHER, J P 2010 Weakly nonlinear dynamics of thermoconvective instability involving viscoplastic fluids. *Journal of Fluid Mechanics* **660**, 316–353.
- MITSHITA, R. S., MACKENZIE, J., ELFRING, G. & FRIGAARD, I. A. 2021 Fully turbulent flows of viscoplastic fluids in a rectangular duct. *Journal of Non-Newtonian Fluid Mechanics* **293**, 104570.
- NOUAR, C & BOTTARO, A 2010 Stability of the flow of a Bingham fluid in a channel: eigenvalue sensitivity, minimal defects and scaling laws of transition. *Journal of Fluid Mechanics* **642**, 349–372.
- NOUAR, C & FRIGAARD, I A 2001 Nonlinear stability of poiseuille flow of a bingham fluid: theoretical results and comparison with phenomenological criteria. *Journal of Non-Newtonian Fluid Mechanics* **100** (1-3), 127–149.
- NOUAR, C, KABOUYA, N, DUSEK, J & MAMOU, M 2007 Modal and non-modal linear stability of the plane Bingham–Poiseuille flow. *Journal of Fluid Mechanics* **577**, 211–239.
- OISHI, C. M., MARTINS, F. P. & THOMPSON, R. L. 2017 The “avalanche effect” of an elastoviscoplastic thixotropic material on an inclined plane. *Journal of non-Newtonian Fluid Mechanics* **247**, 165–177.
- PEIXINHO, J., NOUAR, C., DESAUBRY, C. & THRON, B. 2005 Laminar transitional and turbulent flow of a yield-stress fluid in a pipe. *Journal of non-Newtonian Fluid Mechanics* **128**, 172–184.
- ROSTI, M., IZBASSAROV, D., TAMMISOLA, O., HORMOZI, S. & BRANDT, L. 2018a Coherent structures in the turbulent channel flow of an elastoviscoplastic fluid. *Journal of Fluid Mechanics* **853**, 488–514.
- ROSTI, M E & BRANDT, L 2017 Numerical simulation of turbulent channel flow over a viscous hyper-elastic wall. *Journal of Fluid Mechanics* **830**, 708–735.
- ROSTI, M E, BRANDT, L & PINELLI, A 2018b Turbulent channel flow over an anisotropic porous wall – drag increase and reduction. *Journal of Fluid Mechanics* **842**, 381–394.
- ROSTI, M E, IZBASSAROV, D, TAMMISOLA, O, HORMOZI, S & BRANDT, L 2018c Turbulent channel flow of an elastoviscoplastic fluid. *Journal of Fluid Mechanics* **853**, 488–514.
- RUDMAN, M & BLACKBURN, H M 2006 Direct numerical simulation of turbulent non-newtonian flow using a spectral element method. *Applied Mathematical Modelling* **30** (11), 1229–1248.
- RUDMAN, M, BLACKBURN, H M, GRAHAM, L J W & PULLUM, L 2004 Turbulent pipe flow of shear-thinning fluids. *Journal of Non-Newtonian Fluid Mechanics* **118** (1), 33–48.
- SARAMITO, P 2007 A new constitutive equation for elastoviscoplastic fluid flows. *Journal of Non-Newtonian Fluid Mechanics* **145** (1), 1–14.

- SARAMITO, P 2009 A new elastoviscoplastic model based on the herschel–bulkley viscoplastic model. Journal of Non-Newtonian Fluid Mechanics **158** (1), 154–161.
- SARAMITO, P 2016 Complex fluids. Springer.
- SARAMITO, P & WACHS, A 2016 Progress in numerical simulation of yield stress fluid flows. Rheologica Acta pp. 1–20.
- SARAMITO, P. & WACHS, A. 2017 Progress in numerical simulation of yield-stress fluid flows. Rheologica Acta **56**, 211–230.
- SCHMID, P. 2007 Nonmodal stability theory. Annual Review of Fluid Mechanics **39**, 129–162.
- SHAHMARDI, A, ZADE, S, ARDEKANI, M N, POOLE, R J, LUNDELL, F, ROSTI, M E & BRANDT, L 2019 Turbulent duct flow with polymers. Journal of Fluid Mechanics **859**, 1057–1083.
- SHU, C W 2009 High order weighted essentially nonoscillatory schemes for convection dominated problems. SIAM Review **51** (1), 82–126.
- SINGH, J., M., RUDMAN & BLACKBURN, H. M. 2017 The effect of yield stress on pipe flow turbulence for generalised newtonian fluids. Journal of non-Newtonian Fluid Mechanics **249**, 53–62.
- SUGIYAMA, K, II, S, TAKEUCHI, S, TAKAGI, S & MATSUMOTO, Y 2011 A full Eulerian finite difference approach for solving fluid–structure coupling problems. Journal of Computational Physics **230** (3), 596–627.
- TABUTEAU, H., COUSSOT, P. & DE BRUYN, J. R. 2018 Carbopol: from a simple to a thixotropic yield stress fluid. Journal of Rheology **62**, 773–780.
- VIRK, P S 1971 Drag reduction in rough pipes. Journal of Fluid Mechanics **45** (2), 225–246.
- VIRK, P S 1975 Drag reduction fundamentals. AIChE Journal **21** (4), 625–656.
- WARHOLIC, M D, MASSAH, H & HANRATTY, T J 1999 Influence of drag-reducing polymers on turbulence: effects of Reynolds number, concentration and mixing. Experiments in Fluids **27** (5), 461–472.
- WHITE, C M & MUNGAL, M G 2008 Mechanics and prediction of turbulent drag reduction with polymer additives. Annual Review of Fluid Mechanics **40**, 235–256.
- XI, L & GRAHAM, M D 2010 Active and hibernating turbulence in minimal channel flow of Newtonian and polymeric fluids. Physical Review Letters **104** (21), 218301.
- XI, L & GRAHAM, M D 2012a Dynamics on the laminar-turbulent boundary and the origin of the maximum drag reduction asymptote. Physical Review Letters **108** (2), 028301.
- XI, L & GRAHAM, M D 2012b Intermittent dynamics of turbulence hibernation in Newtonian and viscoelastic minimal channel flows. Journal of Fluid Mechanics **693**, 433–472.
- ZADE, S., SHAMU, T., LUNDELL, F. & BRANDT, L. 2020 Finite-size spherical particles in a square duct flow of an elastoviscoplastic fluid: an experimental study. Journal of Fluid Mechanics **883**, A6.
- ZHU, C., YU, Z., SHAO, X. & DENG, J. 2020 Interface-resolved numerical simulations of particle-laden turbulent flows in a vertical channel filled with bingham fluids. Journal of Fluid Mechanics **883**, A43.